


INFINITE




SYSTEMS

FRM 215

High Efficiency Bi-Amplified Two-Way speaker system, trapezoidal MDF reduced resonance enclosure, loaded with a 15" Neodymium Magnetic low frequency transducer and a 1.4" exit Neodymium Magnetic Titanium Diaphragm compression driver with a 4" voice coil, mounted on a 90° x 60° constant directivity horn. Integral rigging points for safe overhead suspension. Available in any texture finish color, 316L Stainless Steel Grille, 5-year Limited Warranty.



TOP



FRONT



SIDE

TECHNICAL DATA

Utility	Bi Amplified Two-way Speaker System
Configuration	15" LF Transducer and 1.4" Exit HF
Nominal Impedance	8 ohm LF / 8 ohm HF
Rated Power RMS	1200W LF/ 240 W HF
Sensitivity 1W/1M	97.5 db LF / 108 db HF
Applied Range	40Hz to 20000Hz
Coverage	90° x 60°
Connectors	NL-4
Net Weight	82 lbs
Finish Color	Textured Black or Custom
Grille/Protection	316L Stainless
Warranty	60 Month Limited Commercial
Dimensions	18.97" W X 18.75" D X 30" H

WP WEATHER PROTECTED VERSION

- Constructed of Treated Exterior Composite wood panel, which is vermin, termite and mold resistant, without sounding like plastic or fiberglass.
- 316L Stainless Steel Grille for maximum corrosion resistance in the harshest environments.
- 1/4" acoustically transparent foam water stop layer.
- 100 micron 316L Stainless Steel Mesh for insect resistance in outdoor use within landscape environments.
- Weatherized component treatment for long term reliability.
- Watertight junction box for secure connections and vandal resistance on larger properties.
- All Stainless Steel Hardware for reliable, long term outdoor installation.